Boltaron® 9815 N with Pressed Texture

FAR RATED HIGH IMPACT SHEET FOR AIRCRAFT INTERIORS

CHARACTERISTICS

- Provides outstanding durability and long service life
- Consistent, uniform high quality appearance
- Maintains wall thickness integrity in deep draw forming
- Available in a full range of colors, finishes
- Reliable lot-to-lot color consistency
- Customizable in the industry's widest collection of textures
- Safe to use UV-C disinfection

PERFORMANCE DETAILS

FAR RATINGS

| FAR 25.853(a)(i) | (Flammability) (Vertical burn, 60 sec) Pass |
|------------------------|---|
| FAR 25.853(a)(ii) | (Flammability) (Vertical burn, 12 sec) Pass |
| FAR 25.853(d)(Part IV) | (OSU Heat Release) (Peak - HRR, kW/m² <65) (2 Min - HRR, kW min/m² <65) |
| FAR 25.853(d)(Part V) | (NBS Smoke) (Ds Max <200) |

PROPERTIES

| Specific Gravity (ASTM D792) | 1.46 | |
|--------------------------------------|------------------------|---------------------|
| Tensile Strength (ASTM D638) | 6,500 psi | 44.8 MPa |
| Flexural Strength (ASTM D790) | 10,100 psi | 60 MPa |
| Flexural Modulus (ASTM D790) | 409,000 psi | 2,827 MPa |
| Hardness Rockwell R (ASTM D785) | 106 | |
| Heat Deflection Annealed (ASTM D648) | 166 °F @264 psi | 74.4 °C @1.8 MPa |
| Izod Impact Notched (ASTM D256) | 73 °F 3.26 ft-lb/in | 23 °C 174 J/m |

* Independent lab tests. All tests at 73 °F (23 °C) in dry conditions unless otherwise noted.

SHEET SIZES

| Lengths | to 120 in | 3,048 mm |
|---------|---------------------------------|------------------------|
| Widths | to 48 in | 1,219 mm |
| Gauges | from 0.040 to 0.125 in | from 1.02 to 3.2 mm |
| Custom | Custom sizes and gauges availab | le on request |

* Pressed texture lengths available 99 or 122 in (2,514 or 3,099 mm) and widths up to 50 in (1,270 mm) depending on the pattern.

CLEANING AND DISINFECTING BOLTARON® MATERIALS

Boltaron® materials can be cleaned and disinfected safely using many of the recommended methods promoted by the CDC. For more information on cleaning best practices, visit https://www.boltaron.com/careandmaintenance/cleaning-and-disinfecting/.



DISCLANER AND LIMITATION OF WARRANTY. All information contained herein is believed by SIMONA BOLTARON Inc. to be reliable. Typical properties are based on laboratory tests conducted on material samples in accordance with standard test methodology. SIMONA BOLTARON Inc. makes no express or implied warrany that its products will perform in accordance with the data in all conditions and circumstances. To determine suitability for use, users must test applications under actual operating conditions. As a result, ALL EXPRESS OR IMPLIED WARRANTIES IN CONNECTION WITH SIMONA BOLTARON Inc. PRODUCTS INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESS VI DISCLAIMER. M 1.2.2.4

USES

- Aircraft interior seat parts
- Video monitor shrouds
- Galley and lavatory components
- Bull noses, gap covers and moldings
- Class dividers and bulkhead laminates
- Tray tables



9

S



FAR 25.853 (d) aircraft seat parts



DESIGN OPTIONS

| Colors | Unlimited |
|----------|-------------------------|
| Textures | Wide Range Available |
| Effects | True Pearl |
| lmages | Impress Printing® |
| Minimum | 500 lb |

